

## **MANTIS**

**Multispectral Infrared Imaging Camera** 

## Multispectral IR Camera

- Broad coverage range in MWIR & LWIR (2um 12um)
- Uncooled detector, 640 x 480 pixel array
- Low size, weight and power
- Optical design leverages exclusive chalcogenide materials and maintains focus across all wavelengths
- Capture multiple modalities in one camera
- Target applications include use with drones for thermal imaging, laser beacon recognition and threat detection
- Customized cores and lens assemblies are available









800-472-3486



sales@lightpath.com





## GLOBAL LEADER

OPTICS & INFRARED SOLUTIONS

## **Nominal Design Summary**

Parameter	Notes	Design	Unit
Waveband	Multispectral (MWIR –LWIR)	2 –12	μm
Lens EFL	Magnification-based	19	mm
Lens F/#	Aperture-based	f/1.1	
Detector Resolution	Horizontal x Vertical / Pitch	640x480 / 17µm	pixels
Field of View	Vertical FOV	24.3	deg
	Horizontal FOV	32.0	deg
	Diagonal FOV	39.3	deg
Lens Distortion	Max over Full Field (corner)	2	%
Relative Illumination	At HFOV	83	%
	At Corner Field	77	%
Size	Camera (length x height x width)	~49 x 52 x 64	mm
	Lens (diameter x length)	~25 x 25	mm
Weight		< 200	g
Power Consumption		1.1	W





www.lightpath.com



800-472-3486



sales@lightpath.com

